

# Adhesive Grease Spray

## Haftsprühfett

**Product properties:** This product is a fully-synthetic, strongly adhesive lubricant for all joints, hinges, chains and many more. The product forms a long-lasting centrifugal and high-pressure resistant protection layer that repels water, is resistant to heat and salt, reliably protects against corrosion and considerably reduces wear and tear.

**Applications:** Perfectly suitable for lubrication of uncovered sections. For ropes, chains, cables, belts, gearboxes, cranes, construction machinery as well as for motorbikes and bicycles.

**Directions for use:** Thoroughly clean the areas to be treated before application. Then spray the product evenly onto the areas to be lubricated. Shake can well before use.

**Consumption:** approx. 5 – 30 ml per application

**Reaction time:** approx. 30 – 60 sec.

**Sensitive to frost:** no

**Available sizes:** 400 ml



### PRO-TEC Deutschland GmbH

Gewerbegebiet Aschbach  
 07338 Großgeschwenda  
 Tel.: 03 67 35/ 4 44-0  
 Fax: 03 67 35/ 4 44-44  
[info@PRO-TEC-Deutschland.de](mailto:info@PRO-TEC-Deutschland.de)  
[www.Pro-Tec-Deutschland.com](http://www.Pro-Tec-Deutschland.com)